

# TBS

MANOEUVRABLE AND MOBILE. THE TBS.



The Schechtl TBS is the smallest in our range of manual segment swivel bending machines, but a giant when it comes to flexibility on the job site. Its compact dimensions allow you to move the TBS around easily on the job site – between floors, on scaffolding and in small areas. Moreover, the TBS can be installed on a workbench or in a construction vehicle.

## BENEFITS

- ✓ Bending **boxes, cassettes & co.** on the job site
- ✓ **Rational and productive** – all segments are adjusted without the use of tools
- ✓ **Without effort:** 1 man working alone can transport the TBS quite easily
- ✓ **Flexible:** Easy installation on any workbench or in a van
- ✓ **Safe storage** of the segments in a separate case

## TECHNICAL DATA

Subject to change

| MODEL                 | TBS                                     |    | 125  | 100  |
|-----------------------|-----------------------------------------|----|------|------|
| <b>WORKING LENGTH</b> |                                         | mm | 1250 | 1000 |
| <b>OUTPUT</b>         | Steel (400N/mm <sup>2</sup> )           | mm | 0,63 | 0,63 |
|                       | Stainless steel (600N/mm <sup>2</sup> ) | mm | 0,50 | 0,50 |
|                       | Cooper (300N/mm <sup>2</sup> )          | mm | 0,80 | 0,80 |
|                       | Aluminium (250N/mm <sup>2</sup> )       | mm | 1,00 | 1,00 |
|                       | Zinc (150N/mm <sup>2</sup> )            | mm | 1,00 | 1,00 |
| <b>DIMENSIONS</b>     | Length                                  | mm | 1369 | 1235 |
|                       | Depth                                   | mm | 698  | 698  |
|                       | Overall height                          | mm | 1156 | 1133 |
| <b>WEIGHT</b>         |                                         | kg | 114  | 84   |
| <b>CLAMPING BEAMS</b> | Opening height                          | mm | 45   | 45   |

# SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Segments with quick clamping system
  - ✓ Segment box
- 

## ADD-ONS - OPTIMISE YOUR TBS

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
  - ✓ X-shaped support stand
  - ✓ Stand bases
- 

All details onTBS